

Specify Part Number

LBB 3330/00
LBB 3330/50



LBB 3330/00 shown

LBB 3330 Delegate Unit

The LBB 3330 Delegate Unit enables delegates to speak and listen to meeting proceedings via a loudspeaker or headphones. This stylish and ergonomically-designed unit includes a microphone with a red indicator ring which illuminates when the microphone is on. To prevent acoustic feedback, the built-in loudspeaker is muted when the microphone is on. Two 3.5 mm (0.14 in.) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected, so two delegates can simultaneously use the unit. The headphone volume level can be adjusted on the unit for maximum comfort. It is also possible to connect a tape recorder to one headphone socket, and use the other headphone socket to listen to the proceedings.

Delegate Unit Features

- Compact, attractive design
- Flexible mic stem with light ring
- Built-in loudspeaker
- Two headphone sockets
- Built-in volume control for headphones

Specify Part Number

LBB 3331/00
LBB 3331/50



LBB 3331/00 shown

LBB 3331 Chairman Unit

This stylish and ergonomically-designed chairman unit enables the user to function as chairman of a conference or meeting. Similar in appearance to the LBB 3330 Delegate Unit, the LBB 3331 Chairman Unit also includes a "chairman priority" button. When pressed, the priority button causes all currently active delegate microphones to be temporarily or permanently muted, allowing the chairman to take control of the meeting. An optional chime can be selected to precede chairman priority calls.

Chairman Unit Features

- Priority button for chairman
- Delegate mic mute options
- Optional chime tones precede chairman announcements
- Includes all functions of LBB 3330/00
- Flexible mic stem with light ring

Listen Technologies Corporation

14912 Heritagecrest Way
Salt Lake City, UT 84065-4818 U.S.A.
Phone: 1.801.233.8992 or 1.800.330.0891
Fax: 1.801.233.8995
Email: info@ListenTech.com

Don't miss a single sound.



Specifications

Interconnection	Cable type	6 ft. (2 m) cable terminated in a molded 7-pole circular connector for connection to delegate unit or CPSU.
	Connector type	7-pole circular female socket for loop-through connection to delegate units. Two 3.5 mm (.14 in) stereo headphone sockets.
Mounting	mounting type	table top (portable or fixed mounting)
Physical	Dimensions (H x W x D)	2.5 x 4.9 x 6.8 in. (63 x 124 x 172 mm) without microphone. Height is 5 in. (127 mm) with microphone in position (/00 units).
	Length of microphone from mounting surface	12.3 in (313 mm) LBB 3330/00 and LBB 3331/00 microphone length is 12.2 in. (309 mm) LBB 3330/50 and LBB 3331/50 microphone length is 19.2 in. (488 mm)
	Weight	2 lbs. (0.9 kg)
	Color	cover: charcoal base: black

Photographs, CAD drawings, etc. available at www.ListenTech.com.

Accessories



LBB 3310 Control & Power Supply Unit

The Control and Power Supply Unit (CPSU) is the heart of a discussion system. This versatile unit incorporates a digital acoustic feedback suppression facility (LBB 3310/10 only), which allows any acoustic feedback (also known as "howling") to be automatically eliminated. Also available without feedback suppression (LBB 3310/00).



LBB 3312/10 Transport & Storage Suitcase

This transport and storage suitcase is for use in applications where CCS 800 Ultra contribution units will not be used in one fixed location.



LBB 3316 Extension Cables

Extension cable gives additional flexibility using the CCS 800. Cables are terminated at both ends. Available in 2 lengths, 16 ft. (5 m) (LBB 3316/05) and 32 ft. (10 m) (LBB 3316/10) are available to give additional system flexibility in larger application sites. Also available in 328 ft. (100 m) raw cable (LBB 3316/00) without connectors.